CONVAIR A Division of General Dynamics Corporation (San Diego)

DESIGN INFORMATION BULLETIN

NO. 22-2 3,005

REPORT NO. ZM-22-005

DATE: 12 July 1960

MODEL 22- AIRPLANE

PAGE: 1 of 4

SKYDROL 500 CONTAMINATION AREAS

This D.I.B. defines the zone where components and airframe areas are subject to hydraulic system leakages or (servicing) spillage or vapors.

- Zone identification shall be as shown on Figure 1 ("Maintenance Zones") and shall be considered as contamination areas in accordance with Table 1 designation.
- Each design group shall be responsible for the selection of Skydrol resistant materials and processes suitable for parts and assemblies located in the Skydrol areas as indicated in Table 1.
- Compatability information on materials and processes for use in Skydrol areas may be obtained from Value Engineering personnel concerned.

Prepared By R. S. Oberst

Hydraulic Design Group

Approved By: 1)

H. E. Wright Sr. Group Engineer Hydraulic Des. Grp.

Sr. Group Engineer Structural Des. Gri

. Hawkins

Sr. Group Engineer Controls Des. Grp.

C. Hoover

Sr. Group Engineer Furnishings Group

B. B. Shaffer Sr. Group Engineer Electrical Systems

D. G. Moody

Sr. Group Engineer Avionics Group

B. Hurt

Sr. Group Engineer Prop. & Prop. Fluids

D. Krause

Sr. Group Engineer

Environmental Control

. R. Carpenter Sr. Group Engineer Value Engineering

J. T. Heady.

Project Engineer - Model 22

NCITA	
DESIGNATION	
AREA D	
INATED	

																						_										
	INTERIOR		*57	ງ ເທ	ט ני	တေတတ္တတ္တတ္တ											Skydrol 500	Potential Skydrol 500 Contamination. \(\Delta\) Skydrol 500 Contemination. (i.e. due to broken line. or loose fittings. Rear Spar (Aft side only.) No exposure to Skydrol.														
0	EXTERIOR		*52	K	S C	, K	, v	, K	Z Z	ž.	S S	2					= Potential		= Skydrol 50	(1.e. due	or loose F	= Rear Spar	= No exposure									
	ZONE		72.0		£ 60	33 () %	\$ C) 6 0	24 60 60 60 60 60 60 60 60 60 60 60 60 60	. 60	}				CODE:			" (v)	60		RS :								3	P	
			22					¥																								
NCT.LANDTER	INTERIOR		1	<u></u>	-		1	1	!	1	!	-	-	ŧ	1		ď	, v	တ	Ø	(X)	, o	· va	e co	1		- 22	ď	*5			
CANTACTNATED AREA DESIGNATION	EXTERIOR		PS	SS	PS(RS)	PS(RS)		ŀ	1	82	PS		1	1	PS	23	PS	PS	PS	PS	PS	PS	8	S.	വ	S	PS	PS	PS	25	28	
CONTRA	ZONE		35	36	37	38	07	7	77	43	7	45	97	27	20	510	520		240					610	62	63	0,79		20	77		
	2.5						10	-				117						19	1			20					<u></u>					
SS 99	INTERIOR	\$ 1	1	ស	82	PS	တ	ഗ	ty)	PS	PS		-	*2	् 	Ŋ	1	-	20	1	1	1	1	1	1	i	ł	ł	E E	9		
	EXTERIOR		82	PS	PS	23	82	PS	ß	တ	1	PS	PS	PS	co	S	ഗ	ഗ	ł	!	I	1	χ. •	1	PS(RS)	PS(RS)	S.	PS	ഗ	•		
	ZONE		-1	7	3	4	2	9	7	∞	10	11	12	13	77	15	91	17	20	21	22	23	77	25	30	31	35	33	34		*	
- 1	1				1.0													12						-						- 1		

*13, 70, 71, 72 = No contamination on 22-1, -2.

NO:

DATE:

PAGE:

22-2 3.005

12 July

2 of 4

A Potential defined as areas susceptible to Skydrol contamination such as areas 11 & 12 being wetted with Skydrol because of leakage in Nose Wheel Well when airborne.

O Refer to Page 3 for specific limitations set for the indicated zones.

C O N V A I R A Division of General Dynamics Corporation (San Diego)

DESIGN INFORMATION BULLETIN

NO: 22-213 005

REPORT NO. ZN-24-005

DATE: 12 July 1960

MODEL 22 AIRPLANE

PAGE: 3 of 4

SKYDROL 500 CONTAMINATION AREAS

Specific limitations for Skydrol contamination in the following zones.

Zones 51 through 56 - interiors all limited to "S Classification" contamination as follows:

Zone 52 & 5	3 - limited to aileron nose sect of front spar.	tion and forward side
Zone 51	outboard - lefthand flap and spoiler	Limited to exposed areas of nose section
Zone 53	inboard - lefthand flap and spoiler	and forward side of front spar of each flap.
Zone 54	- inboard - righthand , flap and spoiler	
Zone 56	outboard-righthand flap and spoiler	
Zone 60	- outboard - lefthand	
<i>5018</i> 00	horizontal stabilizer	Limited to inboard
		end face.
Zone 65	- outboard - righthand	,I/
	horizontal stabilizer	
GME D STORY		
Zone 61	lefthand - elevator	Limited to inboard en
Zone 64	righthand - elevator	surfaces, forward sidespar and exposed area nose section.
Zone 72	- rudder	Limited to bottom end
		surface, exposed areas of nose section, and forward side of spar.
N STEEL SEL	X	The second secon
		v.

